



INTERNATIONAL STONEWORKS, INC.

2523 FAIRWAY PARK, SUITE 510 * HOUSTON, TEXAS 77092
TEL: (713) 956-8291 * 1-800-775-TILE * FAX: (713) 956-8293
www.intlstoneworks.com * email: sales@intlstoneworks.com

TILE GLOW® #2

TILE GLOW® #2 is a natural, non-wax compound for the polishing and restoration of most unglazed **Ceramic, Porcelain and Quarry Tiles**.

Tile Glow® #2 gives a long-lasting shine, protects and provides a slip resistant finish to ceramic tiles. It does not yellow. The **Tile Glow® Maintenance Program** eliminates the need for constant waxing and stripping of tiles. To apply **Tile Glow® #2**, you need:

1. **Tile Glow® #2**
2. Floor buffer (175 to 350 RPM). Water tank and splash guard optional.
Note: A heavier buffer will give you a quicker and better polish.
Optimum weight of 140 lbs.
3. Wet vacuum, clean mop, bucket, wringer, floor squeegee
4. Natural hair pad; white pad

Directions

Note: The tile and baseboards should be stripped of all waxes or sealers and neutralized.

1. Cover baseboard, carpet, etc., with protective plastic and/or tape.
2. If the grout is very dirty, scrub the grout and tile with our MDR (Mineral Deposit Remover) or TGR (Tile & Grout Restorer) and a scrubbing brush. Wet vacuum and rinse.
3. If the floor is very dirty or old, thoroughly clean and hone the tile with **Tile Glow® #1**. See Tile Glow® #1 instruction sheet.
4. Wet a 25 Sq. Ft. area of the tile. Place a handful of **Tile Glow® #2** on the wet area (5 oz. /25 Sq. Ft.)
5. Buff the **Tile Glow® #2** slurry with a natural hair pad for 15 to 20 minutes per 25 Sq. Ft.
6. Check the level of gloss with the squeegee. When the desired level of gloss is achieved, squeegee the **Tile Glow® #2** slurry to the adjacent area and repeat process. Add **Tile Glow® #2** and water as needed.
7. Vacuum-dry the **Tile Glow® #2** mixture. Wet again polished area and buff again with the same pad without adding more **Tile Glow® #2** to remove residue. Adding some MDR or TGR (1 pint per 5 gallons of water) will speed up the rinsing process and further clean the grout.
8. Vacuum-dry thoroughly, damp mop and let dry.
9. Buff polished area with a dry white pad.
10. If needed, seal the grout with our SEAL & GO® S water/stain repellent penetrating sealer.

Note: Tile Glow® #2 is available in white, gray or black to suit grout colors.

Technical Specifications: see Material Safety Data Sheet. Store in a dry place

Precaution: The use of gloves and protective goggles is recommended when using Tile Glow® #2.

Warning: Avoid contact with skin, eyes and clothes. In case of contact, flush thoroughly with water and call Physician. Do not swallow. Keep out of children's reach.

International Stoneworks, Inc., will not be liable for any damage ensuing to property or injury to operator or any other person due to the misuse or misapplication of Tile Glow® #2 or any other chemical sold by them.