



International Stoneworks

2523 Fairway Park Dr # 510
Houston, TX 77092 USA
1-(713) 956-8291

PRODUCT DATA SHEET

SEAL & GO® S

HEAVY DUTY EXTERIOR SOLVENT BASED SEALER

DESCRIPTION: SEAL AND GO® S is a solvent-based sealer for exterior/interior natural stone, marble, granite, limestone, brick, slate, saltillo, unglazed tile, grout and masonry surfaces. SEAL AND GO® S is not a surface coating but forms a vapor permeable barrier to resist water and stains.

-
- | | |
|---------------------------------------|---------------------------------------|
| ☺ Excellent Stain Protection | ☺ Inhibits Efflorescence |
| ☺ Deep Penetrating | ☺ Interior and Exterior Use |
| ☺ Preserves Natural Appearance | ☺ Weather Resistant |
| ☺ Excellent Water Barrier | ☺ Mild Odor |
| ☺ Vapor Permeable (Breathable) | ☺ Non-Yellowing/U.V. Resistant |
-

TYPICAL APPLICATIONS

Note: To insure product performance and satisfaction, Always pre-test this product in an inconspicuous area. User must determine suitability of product for their intended use.

Before applying SEAL AND GO® S, make sure all surfaces to be treated are thoroughly clean and completely dried. Protect neighboring surfaces not to be treated.

- Apply and saturate all surfaces with SEAL AND GO® S allowing it to puddle and completely saturate the entire surface. SEAL AND GO® S can be applied with a paint brush, paint roller, paint pad/applicator, clean towel or low pressure sprayer with no more than 25 psi.
Note: Do NOT Aerosolize.
- Allow SEAL AND GO® S to absorb and penetrate the entire surface (10-15)minutes. Wipe up any excess by wiping the surface with a clean towel.
- Allow a minimum of two (2) hours drying time.
- For maximum protection, apply a second coat of SEAL AND GO® S to the entire surface, allowing it to penetrate and absorb. Make sure all surfaces are evenly coated. Some areas may absorb more quickly than others.
- Allow 24 hours for SEAL AND GO® S to completely dry and cure for best results.

COVERAGE

Application rates for natural stone, tile, grout and masonry will vary depending on the porosity of the substrate to be treated. Some stone and grout areas will absorb more quickly than other areas.

Approximate Coverage Per Coat

Low Porosity	800-1200	sq. ft/gallon
Medium Porosity	400-800	sq. ft/gallon
High Porosity	100-400	sq. ft/gallon

Note: Less Sealer will be needed when applying a second coat.

Re-apply **SEAL AND GO® S** as needed depending on area usage.

MAINTENANCE Natural stone needs to be cared for properly. While **SEAL AND GO® S** will prevent general soiling, the use of **INTERNATIONAL STONWORKS CLEANERS** is highly recommended for longevity of stain protection. Natural stone, tile, grout and masonry will repel stains and soils effectively when proper cleaning products and methods are used. This application does not eliminate the need for routine cleaning and maintenance. **INTERNATIONAL STONWORKS** makes a full line of products for stone protection and maintenance.

**SAFETY
PRECUATIONS**

- ☞ KEEP OUT OF REACH OF CHILDREN.
 - ☞ COMBUSTIBLE LIQUID AND VAPOR! Keep away from heat, sparks and flames. Eliminated all sources of ignition – heat, sparks, flames, electricity, friction and static. Do not smoke when using.
 - ☞ Do not use this product with high pressure sprayers. Use low pressure sprayers with no more than 25 psi. Do NOT Aerosolize.
 - ☞ Do not breathe spray or mist. Use this product with adequate ventilation. When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection
 - ☞ READ MSDS BEFORE USING. Use only as directed. Wear protective gloves, goggles and respirator when using. Avoid eye and skin contact. Do not breathe mists or spray. Keep container closed when not in use. Store in a cool dry area.
 - ☞ Protect and cover surfaces not to be treated by this product.
-

**TECHNICAL
SUPPORT** For additional technical support, contact International Stoneworks at 1-(713) 956-8291 Monday – Friday from 8:30am-5:00pm EST.

*The information contained herein is based upon practical experience with **SEAL AND GO® S**. It does not constitute a guarantee. Purchasers shall determine the suitability of such products for their own purposes. User assumes all risks and liability whatsoever in connection therein. Manufacturer shall not be liable for any injury or inability to use this product.*