



INTERNATIONAL STONEWORKS, INC.

8650 FAIRBANKS NORTH HOUSTON HOUSTON, TEXAS 77064

TEL: (713) 956-8291 1-800-775-TILE FAX: (713) 956-8293

www.intlstoneworks.com email: sales@intlstoneworks.com

S.A.C.

STAIN ABSORBING COMPOUND

This product is designed to eliminate organic stains such as coffee, tea, oil, butter and other non-acid stains from most marble, granite, limestone, travertine and other porous natural stones.

Some stains may be too old or too deep to be eliminated. Should these stains not come out, International Stoneworks might be able to remove them with our professional grinding and polishing system.

- Natural stone stain remover powder. This is not a pre-mixed product.
- Powder designed to eliminate surface organic stains such as oil, grease, butter and other organic, non-acid stains.
- S.A.C. will not remove inorganic stains such as rust or very deep stains. This is not a stone restoration powder. It will not polish the stone. It will not remove etch marks (chemical burns caused by acids such as lemon, vinegar, etc.). More than one application may be needed.

Directions:

1. Clean the stone surface with LAVENET® and a damp sponge
2. Rinse with a damp sponge and water
3. Mix the Stain Absorbing Compound (S.A.C.) powder with Hydrogen Peroxide (3 to 6% volume by weight) to a soft paste
4. Place the mixture on the stain and cover it with a clear plastic wrap
5. Tape the edges of the plastic wrap with masking tape to keep the paste damp
6. Six to eight hours later, remove the plastic and tape and clean the residue with LAVENET® stone cleaner and a sponge. Rinse with clean water
7. At this point, the stained area is wet and therefore darker. It needs to dry. Let area dry for three to four hours. If the stain has diminished, but is not completely gone, repeat the procedure as often as needed

Subsequent Maintenance:

Clean the stone as often as needed with LAVENET®. Seal the stone with SEAL & GO® S water/stain repellent penetrating sealer.

TECHNICAL SPECIFICATIONS

Active Ingredient: Proprietary blend of limestone particles

Read and consult SDS before using.

Usual Maintenance: 1 lb./25 Sq.Ft.

PRECAUTION

THE USE OF GLOVES AND PROTECTIVE CLOTHING IS RECOMMENDED WITH USING S.A.C.

WARNING

AVOID CONTACT WITH SKIN, EYES, CLOTHES. IN CASE OF CONTACT, FLUSH THOROUGHLY WITH WATER AND CALL PHYSICIAN. DO NOT SWALLOW. KEEP OUT OF THE REACH OF CHILDREN AND PETS.

International Stoneworks, Inc., will not be liable for any damage ensuing to property or injury to operator or any other person due to misuse or misapplication of this or any other chemicals sold by them.